

**SECTION 10 14 00
SIGNAGE**

PART 1 GENERAL

1.01 SUBMITTALS AND SAMPLES

- A. Provide one half-scale character as specified for approval prior to installation.
- B. Provide Shop Drawings per Section 01 33 00 – SUBMITTAL PROCEDURES, showing layout, post-mounting locations, etc., for approval.

PART 2 PRODUCTS

2.01 EXTERIOR BUILDING SIGNS

- A. At Entry (See Drawings):
 - 1. Size: 6 and 4 inches high, 1 inch thick.
 - 2. Style: Helvetica, ALL CAPS.
 - 3. Material: Cast aluminum.
 - 4. Finish: Aluminum.
 - 5. Mounting: Pin mount, 1/2" spacer, epoxy set.
 - 6. Provide template
 - 7. Text (See Drawing Elevations):
 - "OREGON ZOO" (4 inch)
 - "VETERINARY" (6 inch)
 - "MEDICAL CENTER" (4 inch)
 - 8. Manufacturer: Metallic Arts

2.02 ROADSIDE SIGNS

- A. Metal Warning Signs:
 - 1. Blue copy on white background. Signage screened on baked enamel finish.
 - 2. Text: "No Parking Fire Lane"
 - 3. .063 inch aluminum sign, 12" x 18".
 - 4. Mount on post.
- B. Manufacturer: Best Sign Systems (970-249-2378) or approved

2.03 ADA SIGNAGE INTERIOR

- A. Provide signage complying with OSSC 1109.15 and ADA Accessibility Guidelines (ADAAG) and ICC/ANSI A117.1/98 surface mounted adjacent to the door.
- B. Style:
1. 8" x 8" Injection molded polystyrene sign panel. Sign panel material shall be 0.125" injection molded, high impact, polystyrene plastic, UV resistant and surface textured with an eggshell matte finish of less than 15 degrees gloss.
 2. 1/2" radius corners.
 3. 1/32" raised text, graphics and Braille complying with ADA Accessibility Guidelines (ADAAG) and ICC/ANSI A117.1/98 including, but not limited to, 0.312" raised tactile characters, 4.0" graphics and 0.625" upper case text and Grade II Braille.
 4. Molded polystyrene frame.
 5. Colors: Architectural Grey frame and panel with white letters and symbols.
- C. Location and Text:
1. Men's Restroom (Room 122; Doors 122A, and 121B):
 - a. Text: MENS
 - b. Graphic Symbols: man, wheelchair
 2. Men's Locker Room (Room 121, Door 121A):
 - a. Text: MEN'S LOCKER
 - b. Graphic Symbols: wheelchair
 3. Women's Restroom (Room 124; Doors 124A, and 123B):
 - a. Text: WOMEN
 - b. Graphic Symbols: woman, wheelchair
 4. Women's Locker Room (Room 123, Door 123A):
 - a. Text: WOMEN'S LOCKER
 - b. Graphic Symbols: wheelchair
 5. Toilet Room (Room 101, Door 101A):
 - a. Text: RESTROOM
 - b. Graphic Symbols: man, woman, wheelchair
- D. Manufacturer: Kroy Signage Systems, Inc.

PART 3 EXECUTION

3.01 INSTALLATION

- A. Install in strict accordance with the manufacturers printed installation instructions and the approved shop drawings.
- B. Post Mounted Signs:
 - 1. U-bolt on 1-2 inch diameter galvanized steel posts set in concrete.
 - 2. Verify height required. Verify local jurisdiction mounting location and height requirements.

END OF SECTION